



TECHNICAL SPECIFICATIONS

General Information

All measurements should be taken in 1/8".

All outside mounted shutters will be delivered at the exact dimensions indicated.

For all inside mounted shutters, the plant will make the necessary deductions (1/4" height, 1/8" width).

Panel Sizes

Minimum panel width: 12"

Max single panel width: 28"

Max bi-fold panel width: 24" for shutters with frames
21" for shutters without frames

Dividers

The invisible divider is available for *Perfect View* only.

A divider rail is required for all single panels over 65" in height.

A divider rail is required for all bifolding panels over 50" in height. A second divider rail is required for bifolding panels over 95" in height.

The divider rail for 2 3/8" louvers measures 3 1/2".

The divider rail for 3 3/8" louvers measures 2 1/2".

Divider locations may vary by a maximum of 1" (up or down) with a 2 3/8" louvers and a maximum of 1 1/2" (up or down) with 3 3/8" louvers.

To ensure a similar appearance of adjacent shutters, i.e. Equivalent top and bottom rail sizes, aligned dividers, and an equal number of louvers, the shutters ordered must be the same height.

Divider locations should be measured in inches from the bottom.

The measurements for shutters with frames must be taken from the bottom of the frame. The measurement for shutters without frames must be taken from the bottom of the panel.